



# M-1 Sealant Resin

## SECTION 1. IDENTIFICATION

<b>Product Identifier</b>	M-1 Sealant Resin
<b>Other Means of Identification</b>	Epoxy Based Resin
<b>Product Family</b>	Epoxy Resin
<b>Recommended Use</b>	Mixed with another component to create a pourable or pumpable product that can be used to seal inserts or repair cracks in concrete structures.
<b>Restrictions on Use</b>	None known.
<b>Manufacturer/Supplier Identifier</b>	The Stebbins Engineering and Manufacturing Company, 363 Eastern Boulevard, Watertown, NY, 13601, (315) 782-3000, www.stebbinseng.com
<b>Emergency Phone No.</b>	Chemtrec - Within North America, 1-800-424-9300, 24 hours Stebbins 24 Hour Contact-, 1-315-788-6624
<b>SDS No.</b>	116

## SECTION 2. HAZARD IDENTIFICATION

### Classification

Acute toxicity (Dermal) - Category 5; Acute toxicity (Inhalation) - Category 4; Skin irritation - Category 2; Eye irritation - Category 2A; Skin sensitization - Category 1; Aquatic hazard (Chronic) - Category 2

### Label Elements



Signal Word:  
Warning

### Hazard Statement(s):

- H313 May be harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.

### Precautionary Statement(s):

- P261 Avoid breathing vapours, spray.
- P264 Wash hands and skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P362 + P364 Take off contaminated clothing and wash it before reuse.

- P273 Avoid release to the environment.  
 P280 Wear protective gloves.  
 P280 Wear eye protection/face protection.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTRE or doctor if you feel unwell.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337 + P313 If eye irritation persists: Get medical advice/attention.  
 P391 Collect spillage.  
 P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Butylated epoxy resin	71033-08--4	> 60		
Bisphenol F / phenol novolac resin blend		< 40		

### SECTION 4. FIRST-AID MEASURES

#### First-aid Measures

##### Inhalation

Move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. Get medical advice or attention if you feel unwell or are concerned.

##### Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Immediately wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 15-20 minutes. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Get medical advice or attention if you feel unwell or are concerned. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

##### Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice or attention.

##### Ingestion

Rinse mouth with water. Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Get medical advice or attention if you feel unwell or are concerned.

#### Most Important Symptoms and Effects, Acute and Delayed

If in eyes: may cause moderate to severe irritation.

If on skin: may cause moderate to severe irritation. Skin sensitizer. May cause an allergic skin reaction in some people.

If swallowed: can irritate the mouth, throat and stomach.

#### Immediate Medical Attention and Special Treatment

##### Target Organs

Eyes, skin.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing Media

##### Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Product Identifier: M-1 Sealant Resin - Ver. 4

SDS No.: 116

Date of Preparation: July 28, 2015

Date of Last Revision: May 27, 2020

Page 02 of 07

### Unsuitable Extinguishing Media

None known.

### Specific Hazards Arising from the Product

Closed containers may rupture violently when heated releasing contents.

In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide.

### Special Protective Equipment and Precautions for Fire-fighters

Dike and recover contaminated water for appropriate disposal.

Fire-fighters may enter the area if positive pressure SCBA and full Bunker Gear is worn.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Increase ventilation to area or move leaking container to a well-ventilated and secure area. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

### Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Minimize the use of water to prevent environmental contamination.

### Methods and Materials for Containment and Cleaning Up

Stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal. Contaminated absorbent poses the same hazard as the spilled product. Review Section 13 (Disposal Considerations) of this safety data sheet.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.

### Conditions for Safe Storage

Comply with all applicable health and safety regulations, fire and building codes. Store in the original, labelled, shipping container. Store in an area that is: dry, cool, well-ventilated, separate from incompatible materials (see Section 10: Stability and Reactivity). Store in a closed container.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Butylated epoxy resin	Not established		Not established			

No exposure limits established.

### Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. General ventilation is usually adequate.

### Individual Protection Measures

#### Eye/Face Protection

Wear approved safety glasses.

#### Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

#### Respiratory Protection

Product Identifier: M-1 Sealant Resin - Ver. 4

SDS No.: 116

Date of Preparation: July 28, 2015

Date of Last Revision: May 27, 2020

Page 03 of 07

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

<b>Appearance</b>	Yellow viscous liquid.
<b>Odour</b>	Sweet
<b>Odour Threshold</b>	Not available
<b>pH</b>	Neutral
<b>Melting Point/Freezing Point</b>	Not available (melting); Not available (freezing)
<b>Boiling point/Initial boiling point</b>	Not available
<b>Boiling Range</b>	Not available
<b>Flash Point</b>	> 200 °F (93 °C)
<b>Evaporation Rate</b>	Not available
<b>Flammability (solid, gas)</b>	Not applicable (liquid).
<b>Upper/Lower Flammability or Explosive Limit</b>	Not available (upper); Not available (lower)
<b>Vapour Pressure</b>	Not available
<b>Vapour Density (air = 1)</b>	Not available
<b>Relative Density (water = 1)</b>	~ 1.11
<b>Solubility</b>	Insoluble in water
<b>Partition Coefficient, n-Octanol/Water (Log Kow)</b>	Not available
<b>Auto-ignition Temperature</b>	Not available
<b>Decomposition Temperature</b>	Not available
<b>Viscosity</b>	Not available (kinematic); Not available (dynamic)
<b>Other Information</b>	
<b>Physical State</b>	Liquid

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

### Chemical Stability

Normally stable.

### Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

### Conditions to Avoid

Prolonged exposure to high temperatures. Freezing. Incompatible materials. Contact with combustible materials. Temperatures above 350.0 °F (176.7 °C)

### Incompatible Materials

Avoid: strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide), strong oxidizing agents (e.g. perchloric acid).

Not corrosive to metals.

### Hazardous Decomposition Products

Very toxic carbon monoxide, carbon dioxide.

## SECTION 11. TOXICOLOGICAL INFORMATION

Product Identifier: M-1 Sealant Resin - Ver. 4

SDS No.: 116

Date of Preparation: July 28, 2015

Date of Last Revision: May 27, 2020

Page 04 of 07

## Likely Routes of Exposure

Skin contact; inhalation; eye contact.

## Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Bisphenol F / phenol novolac resin blend	Not available	> 5,000 mg/kg (male rat)	> 2,000 mg/kg (male rat)
Butylated epoxy resin	Not available	> 5000 mg/kg (rat)	> 2000 mg/kg (rat) (vapour)

## Skin Corrosion/Irritation

May cause mild irritation based on information for closely related chemicals.

## Serious Eye Damage/Irritation

May cause serious eye irritation based on information for closely related materials. The vapour also irritates the eyes.

## STOT (Specific Target Organ Toxicity) - Single Exposure

### Inhalation

May cause nose and throat irritation.

### Skin Absorption

Symptoms may include redness, rash, swelling and itching.

### Ingestion

May cause irritation of the mouth, throat and stomach.

## Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

## STOT (Specific Target Organ Toxicity) - Repeated Exposure

If inhaled, following skin contact and/or if swallowed: once sensitized, an allergic reaction may occur at low exposure levels.

## Respiratory and/or Skin Sensitization

Skin sensitizer. In sensitized people, contact with a very small amount of product can cause an allergic reaction. Symptoms include redness, rash, itching and swelling. This reaction can spread from the hands or arms to the face and body. Repeated exposure will make the reaction worse. Not known to be a respiratory sensitizer.

## Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Bisphenol F / phenol novolac resin blend	Not Listed	Not Listed	Not Listed	Not Listed
Butylated epoxy resin	Not Listed	Not designated	Not Listed	Not Listed

Not a carcinogen.

## Reproductive Toxicity

### Development of Offspring

Not known to harm the unborn child.

### Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

### Effects on or via Lactation

Not known to cause effects on or via lactation.

## Germ Cell Mutagenicity

Not known to be a mutagen.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Acute Aquatic Toxicity

Product Identifier: M-1 Sealant Resin - Ver. 4

SDS No.: 116

Date of Preparation: July 28, 2015

Date of Last Revision: May 27, 2020

Page 05 of 07

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Bisphenol F / phenol novolac resin blend	1.5 mg/L (Daphnia magna (water flea); 96-hour; semi-static)			9.4 mg/L (Desmodesmus subspicatus (algae); 72-hour; static)

#### Persistence and Degradability

Does not degrade rapidly based on quantitative tests.

#### Bioaccumulative Potential

Bioaccumulative potential is low.

#### Mobility in Soil

No information was located.

## SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal Methods

Contact local environmental authorities for approved disposal or recycling methods in your jurisdiction. This product and its container must be disposed of as hazardous waste. Do NOT dump into any sewers, on the ground or into any body of water. Treat waste in an approved waste disposal facility. Dispose of or recycle empty containers through an approved waste management facility.

## SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations. Not regulated under IATA Regulations.

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT		Non-Regulated		
Canadian TDG		Non-Regulated		
IATA (Air)		Non-Regulated		
IMO (Marine)	UN3082	environmentally hazardous substance, liquid, n.o.s. (Bisphenol F Epoxy Resin)	9	III

**Environmental Hazards** Marine Pollutant (Bisphenol F / phenol novolac resin blend)

**Special Precautions** Not applicable

#### Transport in Bulk according to International Maritime Organization Instruments

Not applicable

**Other Information** If all or part of the transportation is by vessel, this material must be classified as "Environmentally hazardous substance, liquid, n.o.s. (bisphenol F epoxy resin), UN3082, Class 9, packing group III," and as a marine pollutant. Otherwise, this material is not regulated for transport.

## SECTION 15. REGULATORY INFORMATION

#### Safety, Health and Environmental Regulations

##### Canada

##### Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Not listed on the DSL or NDSL.

##### CEPA - National Pollutant Release Inventory (NPRI)

Not specifically listed.

Product Identifier: M-1 Sealant Resin - Ver. 4

SDS No.: 116

Date of Preparation: July 28, 2015

Date of Last Revision: May 27, 2020

Page 06 of 07

## USA

### Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

### Additional USA Regulatory Lists

SARA Title III - Section 311/312: Acute Health Hazard. (Butylated epoxy resin)

## SECTION 16. OTHER INFORMATION

<b>NFPA Rating</b>	<b>Health - 2</b>	<b>Flammability - 1</b>	<b>Instability - 0</b>
	<b>Based on</b>	Bisphenol F / phenol novolac resin blend	
<b>SDS Prepared By</b>	B.E.R.		
<b>Phone No.</b>	(315) 782-3000		
<b>Date of Preparation</b>	July 28, 2015		
<b>Date of Last Revision</b>	May 27, 2020		
<b>Revision Indicators</b>	Revision 4 The following SDS content was changed on May 27, 2020: reviewed and approved		
<b>Key to Abbreviations</b>	ACGIH® = American Conference of Governmental Industrial Hygienists HSDB® = Hazardous Substances Data Bank IARC = International Agency for Research on Cancer NFPA = National Fire Protection Association NIOSH = National Institute for Occupational Safety and Health NTP = National Toxicology Program OSHA = US Occupational Safety and Health Administration RTECS® = Registry of Toxic Effects of Chemical Substances		
<b>References</b>	CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS). HSDB® database. US National Library of Medicine. Available from Canadian Centre for Occupational Health and Safety (CCOHS). NIOSH Pocket Guide database. National Institute for Occupational Safety and Health. Available from Canadian Centre for Occupational Health and Safety (CCOHS). Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and Safety (CCOHS).		
<b>Disclaimer</b>	NOTE: The information contained herein is, to the best of our knowledge, accurate and reliable. However, no warranty is expressed or implied regarding the accuracy of this information, or the results to be obtained from the use thereof.		